

RUST PAINT

Painting rust effect

DESCRIPTION

Even rust even wear a symbol representative of a decoration provided by nature.

Now with RUST PAINT we are happy to welcome to rust in the decorative world.

With RUST PAINT rust becomes elegance without to hide it.

The classic that adapts to modern environments.

APPLICATION

- Make sure that the substrate is well dry. In case of plaster, make sure that it has a curing time of at least 28 days, depending on the temperature.
- Make sure that the substrate has been adequately prepared and that it is suitable for painting: dry plaster, have removed any granules from the plaster, in case of old walls make sure that there are no poor or powdery paints, and remove them if any; also remove peeling paints.
- If necessary, apply 1 coat of SCIK PURAL ACRIL insulating material.
- Apply one or two coats of DECOR FONDO primer diluted 5 - 10%. Allow it to dry perfectly (from 6 to 12 hours).

COBRA VERDE EFFECT

- Apply STRUCTURA HI-TECH METALLICO RAME, ready to use, using a short-haired roller.
- Allow to dry for 6-12 hours.
- Apply RUST PAINT, ready to use, using the tool SPALTER 100, distributing the product regularly in different parts of the surface and reproducing movements in alternating stretches with the brush.
- Smooth the freshly applied strokes of RUST PAINT using the SPALTER 100 and directing the product vertically. Repeat the same operation several times to create the characteristic effect of the striping.
- Allow it to dry for 6-12 hours.
- Pour a small quantity of RUST GREEN RAME on a support and impregnate the end of a sponge in the product. Stroke the surface by applying the product vertically.
- Wait 6-12 hours for the complete drying.

RUST PAINT TEMPO

- To recreate the RUST PAINT TEMPO effect, position the TEMPO stencil on the surface. Use a brush to apply RUST PAINT to reproduce the stencil pattern.
- Allow it to dry to appreciate the final effect.

CORTEZA EFFECT

- Apply one coat of RUST VERDE RAME evenly over the entire surface using a short-haired roller.
- Allow to dry for 6-12 hours.
- Apply one coat of RUST PAINT using a roller.
- Line the surface using the FRATTONE CROME tool. The created lines will bring out the coat of GREEN RAME applied below.
- Let dry 6-12 hours.
- Pour a small quantity of RUST VERDE RAME on a support and impregnate the end of a sponge into the product. Stroke the surface by applying the product vertically.
- Allow to dry completely to appreciate the final effect.

PATINA EFFECT

- Apply one coat of STRUCTURA HI-TECH METALLICO RAME ROSSA using a roller evenly on the entire surface.

- Allow to dry for 6-12 hours.
- Apply STRUCTURA HI-TECH METALLICO ORO pouring a small quantity on a support and impregnate the special sponge (SPUGNA MAR MEDITERRANEO) into the product. Dab onto the surface distributing it evenly.
- Repeat the same operation first with the product RUST VERDE RAME and then with the product RUST PAINT.
- Let it dry completely to appreciate the final effect.


DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com

TECHNICAL DATA	
Nature of the bond	Emulsion Acrylic
Viscosity	
Drying Time	1 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	5-6m ² /Lt
Specific weight	1,12Kg/Lt
Colors	Rust
Dry aspect	Rust in various shades effect
Wet aspect	Liquid with rust color
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	30µGr/m ³
TVOC	490µGr/m ³
PH	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,2.5LT
CHARACTERISICS	
Characterisics:	Breathable,Environmentally friendly.
Can be applied on:	Walls,Wood.
for:	Interiors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Spalter 100,Short haired roller.
Related products:	STRUCTURA HI-TECH RAME,SPECIAL RUST PAINT.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.l.

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 03937370751

www.rivedil.com - export@rivedil.com