

SCHEDA TECNICA N°219

AQVADecorative Metal Finishing

DESCRIPTION

AQVA is the new decorative paint with a metallic sheen.

Thanks to the many effects you can achieve, AQVA is suitable as a finish for a modern, classic, ethnic and contemporary environments.

Ideal for decoration of columns, frames and all media where you want to finish with a visible metallic sheen.

AQVA becomes fully washable after three weeks from application.

Available in GOLD, SILVER, COPPER, BRONZE, COPPER RED PAINT.

APPLICATION

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.
- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules, on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc.
- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.
- Apply with a brush or roller one or two coats of DECOR FONDO PRIMER diluted with 5-10 % water.
- Once fully dry, apply AQVA with a brush giving the desired effects. Stroke the brush in an x pattern, half circles, cubes (see catalog) to achieve the desired effect.
- Apply one coat of the product with a spalter 100 brush evenly with irregular brush strokes covering an area of about 1 square meter . Subsequently with the brush back spread the product applied by drawing the desired effect (x pattern, half circles or cubes). Proceed with this technique over the entire surface .

ROLLER EFFECT

- Apply one coat of the product with a short haired roller on the surface with irregular and messy movements.

AQVA EFFECT with SPRAY PAINT or ROLLER

- Thin AQVA with 20-25% of water. Apply the product with a short haired roller or spray on the surface.
- Apply one or two coats .

TECHNICAL DATA	
Nature of the bond	waterborne fine resine
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	3-4m²/Lt
Specific weight	1,131Kg/Lt
Colors	Gold, Silver, Copper, Bronze, Red Copper
Dry aspect	Polished with metallic effects
Wet aspect	Semi-dense Semi-dense
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
voc	110μGr/m³
TVOC	950μGr/m³
РН	7-8°C
Cleaning	Water and Soap
Packing	0.750LT,2LT
CHARACTERISICS	
Characterisics:	Washable, Environmentally friendly.
Can be applied on:	Walls, Wood.
for:	Interiors.
Certifications:	TOW YOU.
TOOLS AND RELATED PROD	UCTS
Tools:	Spalter 70,Spalter 100.
Related products:	DECOR FONDO (WHITE).

CAUTION:

- N.4 The raw materials used are natural and may have small differences depending on the batchs used. Therefore it is recommended to use the same batch of product for the same work to be carried out. Where this is not possible just mix the batches together.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.