

SCHEDA TECNICA N°404

STILE BAROCCO TADELAKT

Decorative plaster based on lime putty

DESCRIPTION

TADELAKT is a decorative plaster based on a lime putty with a high gloss effect. Depending on the application and the colors chosen the product resembles the typical Italian marble.

TADELAKT, being completely composed of lime, is highly breathable and completely natural.

APPLICATION

- Make sure the surface is completely dry . If the surface is plastered, make sure it had a curing time of at least 28 days , depending on temperature.

- Make sure that the media has been well prepared and is suitable for coating: plaster must be dry, not have any granules , on old walls, make sure that there is no poor quality or powdery paint, remove flaking paint etc.

- Apply 1 coat of SCIK PURAL ACRIL primer if necessary.

- Apply with a brush or roller one or two coats of DECOR FONDO PRIMER diluted with 5-10 % water.

- Apply the first coat of TADELAKT dyed using TONER TN or BASE COLOR UPC. Use a stainless steel trowel, taking care to smooth the entire surface.

- Sand with very fine sandpaper any imperfections and brush off the dust.

- Once dry, apply a second coat of TADELAKT creating the typical effects of a lime slate. Therefore you can get the effects of shiny marble, overlapping effects and so on....

TECHNICAL DATA	
Nature of the bond	Vinyl resin
Viscosity	
Drying Time	2 h at touch, 6-12 h complete.
Thinning	Ready to use
Yield	4-5m²/Kg
Specific weight	N/A
Colors	Bianco,to be colored,see color chart
Dry aspect	polished marble
Wet aspect	Pasta in white
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	10μGr/m³
ТVОС	40μGr/m³
РН	11-12°C
Cleaning	Water and Soap
Packing	5KG,20KG
CHARACTERISICS	
Characterisics:	Washable, Environmentally friendly.
Can be applied on:	Walls,Wood.
for:	Interiors/Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Stainless Steel Trowel 200x80cm, Stainless Steel Trowel 240x100cm.
Related products:	DECOR FONDO (WHITE).

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.

- In the original, sealed containers and in appropriate temperature conditions. The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.

- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge, however, being elements such as weather conditions, labor, tools, quality of third party products and others, not under the direct control of the Rivedil, this document does not constitute a warranty, nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document. We recommend that you always check the suitability of the product to each specific instance. This supersedes all previous editions.

DECORAZIONI RIVEDIL S.r.I. Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy Tel. (+39) 0832 731293 - (+39) 0832 731273 P.IVA 03937370751 www.rivedil.com - export@rivedil.com